



TECHNICAL & PRODUCT INFORMATION

MASONRY PAINT

DESCRIPTION

Masonry paint is a flexible decorative protective coating for exterior use. Masonry paint is ideally suited for application to stonework, concrete, brick and timber where an opaque, decorative protective finish is required.

Masonry paint is flexible and developed to withstand severe fluctuations in temperature.

Masonry paint is microporous and will allow the migration of moisture within the underlying surface to escape.

PREPARATION

Do not apply in temperatures below 8°C . Ensure that all surfaces are dry and free from grease.

Remove loose paint and wash if necessary to remove dirt. Smooth, glossy surfaces should be sanded beforehand.

Any porous surface should be treated with a sealer coat and allowed to fully dry before applying Masonry paint.

APPLICATION

Apply with a brush, roller, paint pad or spray equipment. Masonry paint will be touch dry within 1 -2 hours depending on the temperature. In damp or humid conditions drying may take slightly longer. Allow 4 hours between coats and preferably apply a minimum 2 coats for optimum hiding power.

COVERAGE

A 5 litre tin will cover approximately 25-30 m² per coat when applied by brush to sound, non porous surfaces. Roller and spray application will provide greater coverage.

CLEANING

Remove as much paint as possible from equipment before cleaning. Clean brushes, rollers and paint pads with cold water. Clean several times to ensure no paint remains. Flush spray equipment with water thoroughly. Ensure spray guns are free from residual paint.

HEALTH & SAFETY

Ensure good ventilation during application. Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with cold water and seek medical attention. In case of contact with skin, wash with soapy warm water and apply moisturising cream.